EPCOS

Applications

- Switch-mode power supplies

Features

- Close resistance tolerance, improved insulation voltage
- Useable in series connections up to 265 V_{rms}
- Coated thermistor disk
- Kinked leads of tinned copper wire
- Wide resistance range
- UL approval (E69802)

Delivery mode

Bulk (standard),
cardboard tape, reeled or in Ammo pack



Dimensions in mm
Approx. weight 1,7 g

Climatic category (IEC 60068-1)		55/170/56	
Max. power at 25 °C	P_{max}	2,4	W
Resistance tolerance	$\Delta R_N/R_N$	± 15 %	
Rated temperature	T_N	25	°C
B value tolerance	$\Delta B/B$	± 3 %	
Dissipation factor (in air)	δ_{th}	approx. 14	mW/K
Thermal cooling time constant (in air)	τ_c	approx. 50	s
Heat capacity	C_{th}	approx. 700	mJ/K
Test voltage (t = 1 s)	V_T	1000	VDC

R_{25} Ω	I_{max} (0 … 65 °C) A	No. of *R*/*T* characteristic	$B_{25/100}$ K	C_T[1] 230 V µF	C_T[1] 110 V µF	Parameters for *R*(*I*)[1] *k*	*n*	Ordering code
2,5	5,5	1201	2700	200	800	0,621	– 1,27	B57236S0259L002
3,0	5,0	1202	2800	300	1200	0,80	– 1,31	B57236S0309L002
5,0	4,5	1202	2800	300	1200	0,761	– 1,30	B57236S0509L002
8,0	3,7	1203	2900	300	1200	1,11	– 1,34	B57236S0809L002

1) For details on the capacitance C_T as well as on the parameters *k* and *n* refer to “Application Notes”, pages 40 – 42.

Reliability data

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature *T*: 170 °C *t*: 1000 h	< 10 %	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: 40 °C Relative humidity of air: 93 % Duration: 21 days	< 5 %	No visible damage
Rapid temperature cycling	IEC 60068-2-14	Lower test temperature: – 55 °C Upper test temperature: 170 °C Number of cycles: 10	< 10 %	No visible damage
Endurance		$I = I_{max}$ *t*: 1000 h	< 10 %	No visible damage
Cyclic endurance		$I = I_{max}$, 1000 cycles On-time = 1 min Cooling time = 6 min	< 10 %	No visible damage
Transient load		Capacitance = C_T Number of cycles: 1000	< 5 %	No visible damage

zuholen.

Published by EPCOS AG
Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY
☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the E
Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unle

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the i
tives.

Due to technical requirements components may contain dangerous substances. For information on the
also contact one of our Sales Offices.